

FRONT ELEVATION

1/4"=1'-0"



RIGHT ELEVATION

1/4"=1'-0"



REAR ELEVATION

1/4"=1'-0"



LEFT ELEVATION

1/4"=1'-0"



ROOF PLAN

VENT CALCULATIONS:

VENTILATION REQUIRED 1 SF PER 150 SF ATTIC/CEILING AREA.

ATTIC/CEILING AREA: 2200 SF

2200/ 150 = 14.75 SF VENT REQUIRED

IF HALF OF VENT AREA IS LOCATED @ RIDGE & HALF IS LOCATED @ EAVES, VENTING RATIO MAY BE REDUCED TO 1/300.

43 ROOF VENTS, MODEL AF-840 (840SQIN. FREE AREA) ARE NEED TO MEET THE VENTING REQ'S.

ENERGY COMPLIANCE
TABLE N1101.1(1)
PRESCRIPTIVE COMPLIANCE PATH FOR GROUP R-3 OCCUPANCY

MAXIMUM ALLOWABLE WINDOW AREA:	NO LIMIT
WINDOW CLASS:	U = 0.35
EXTERIOR DOORS[m]	U = 0.20
EXTERIOR DOOR W/>2.5' GLAZING[n]	U = 0.40
WALL INSULATION:	R-21
UNDERFLOOR INSULATION:	R-30
FLAT CEILING[i]	R-38
VAULTED CEILING[g]	R-38
SKYLIGHT CLASS:	U = 0.60
SKYLIGHT AREA[i]	<2%
BASEMENT WALLS:	R-21
SLAB FLOOR EDGE INSULATION:	R-15
FORCED AIR DUCT INSULATION:	R-8

SECT. N1107.2
LIGHTING-MIN. 50% TO BE HIGH EFFICENCY FIXURES

ADDITIONAL MEASURES
TABLE N1101.1(2)

ENVELOPE ENHANCEMENT

HIGH EFFICIENCY ENVELOPE

WALL INSULATION:		
VAULTED CEILING:	d.e and	R-49
FLAT CEILING:	and	R-49
FRAMED FLOORS:	and	R-38
WINDOW CLASS:	and	U = 0.30
DOORS:	or	U = 0.20

ADDITIONAL 15% HIGH EFFICIENCY LIGHTING FIXTURES

CONSERVATION MEASURE

HIGH EFFICIENCY HVAC SYSTEM
GAS HEATING UNIT MIN. 90% EFFICIENCY RATING
or AIR-SOURCE HEAT PUMP W/
MIN. HSPF OF 8.5

NO.	DATE	REVISIONS DESCRIPTION	BY

ERNIE JETTE CONSTRUCTION CO.
5858 SE 25th TERRACE, GRESHAM, OREGON 97080 (503) 380-7892 FAX (503) 663-9703

project
SE ALDER ST
ELEVATIONS

plan
1679

1
7/15/16